


► Series SPF

Three-Screw pump for applications up to 40 bar



► Pumped Liquid

Chemically neutral, lubricating, e.g. fuel oils, lubricating oils, hydraulic oils, cutting oils, cooling oils, waxes, tar oils, polyols

► Main Fields Of Application

Firing, hydraulics, mechanical engineering, general industrial technologies, chemical and petrochemical industries, marine and offshore engineering

► Performance Data

Capacity	Q	up to	110	l/min
Inlet pressure	ps	up to	5	bar
Discharge pressure	pd	up to	40	bar
Differential pressure	pdiff	up to	40	bar
Viscosity	v	up to	3..760	mm ² /s
Fluid temperature	t	up to	150	°C
Speed	n	up to	3600	1/min

► Construction features

- Bulkhead mounting
- Pedestal mounting
- Dry installation
- In-tank installation
- Vertical installation
- Horizontal installation
- Self - priming
- With shaft sealing

Document free of charge by phone +49 7732 86-382 fax +49 7732 86-99382

ALLWEILER AG
 PO Box 1140
 D-78315 Radolfzell Germany
 Phone.: +49 (0)7732 86-0
 Fax: +49 (0)7732 86-436
 E-mail: service@allweiler.de
 Internet: <http://www.allweiler.com>